

# SGO-5 SecureSwing S™

## Enclosed Screw Drive Residential Swing Gate Opener

With European styling and clever control logics, the new **SecureSwing S™** Swing Gate Opener is a form and function revolution for wide single and dual leaf swing gates.

### Drive Arms

IP 44 rated drive arms house a 24Vdc motor and robust screw drive system that produces 300daN of torque to drive a 4.0m single leaf up to 300kg in weight.

### Slim Design & Reduced Sideroom

Flush fitting drive arms need little sideroom for installation.

### Soft Start/Soft Stop

Speed ramping reduces stress on the gate and opener.

### Limits Setting

Screw drive mounted switches for accurate position data.

### 100% Duty Cycle

The thermodynamically efficient motor design allows for high duty cycle applications<sup>1</sup>

### Battery Backup

In the event of power failure, the optional battery backup will keep the **SecureSwing S™** functional.

### Solar Power

Be it a location without accessible mains power, or a normal residential application, a solar charging unit with battery backup can power the **SecureSwing S™**.

### Non-Reversing System

Mechanical locks positively secure the screw drive whenever the motor is not running, preventing access or damage.



### Lockable Manual Release

A weather protected key release allows disengagement for manual operation in the event of power failure.

### Logic Control Box

Storing up to 110 transmitters, the logic control box also:

- integrates inputs such as P.E. Beams and loop detectors
- offers auto-close, vacation and pedestrian modes, and control of courtesy lights.



### Specifications - Drive Arm (Order Code #90701)

<b>Power Supply</b>	24Vdc
<b>Power</b>	70W 3A
<b>Torque</b>	300daN
<b>Screw Drive Travel</b>	400mm
<b>Rod Speed</b>	1.6cm/second
<b>Max Leaf Width and Weight</b>	4.0m & 300 Kg
<b>Duty Cycle at 20°C</b>	100% <sup>1</sup>
<b>Single Drive Arm Weight</b>	8.0 Kg
<b>Drive Arm Dimensions (WxHxD)</b>	935 x 105 x 148mm

### Specifications - Logic Control (Order Code #90720/90721)

<b>Receiver Capacity</b>	110 transmitters
<b>Receiver Frequency</b>	433.92 MHz
<b>Coding Type</b>	Code Hopping (non-linear encryption algorithm)
<b>Control Box Weight</b>	4 Kg
<b>Control Box Dimensions (Wx-HxD)</b>	190 x 240 x 100mm

### Warranty (Drive Arms and Control Box)

**Warranty** | 1 year parts

1. 100% duty cycle possible with mains power only. This is not possible when operating via battery backup or with solar.

© June 2007 Automatic Technology (Australia) Pty Ltd. All rights reserved. SecuraCode® and SecureSwing S™ are trademarks of Automatic Technology (Australia) Pty Ltd. No part of this sheet may be reproduced without our prior permission. In an ongoing commitment to product quality we reserve the right to change specification without notice. E&OE.

Order Code Options	
Pack Contents	Order Code
1 x Drive Arm	90701
1 x Drive Arm + 1 x Logic Control Box	90720
2 x Drive Arms + 1 x Logic Control Box	90721